

DRAMM



Discharge Hose
& Spray Gun

Sprayer Pump

Suction Hose
& Filter

- Multi-purpose hydraulic sprayer
- Adjustable pressure- up to 500 PSI
- Adjustable spray pattern and output rate
- Long life pump assembly: corrosion resistant
- Optional Hose Reel Available
- Optional cart and 20 gallon tank available
- Backed by a 6 month warranty on parts and labor

Heavy-Duty Sprayer MS-O Specifications

The Dramm MSO Heavy Duty Sprayer is a powerful and compact hydraulic sprayer designed to apply all formulations of chemicals. The MSO offers a fully adjustable pressure regulator with a maximum pressure of 500psi. Combined with the MS-TG trigger gun and the pump output of 1/2 gpm, the MSO creates a very fine spray for even coverage. The included trigger gun offers an adjustable pattern that will spray from a 20 foot straight stream to a 10 foot mist cone.

The MSO is available in several models. The base unit includes the pump, 33 foot discharge hose and the suction and bypass hoses (model MSO). Additionally, the MSO is

available with a 20 gallon cart and tank (pictured right). The 20 gallon model is available with either 33 feet of hose (model MS20-33) or with 100 feet of hose and a hose reel (model MS20-100). The hose reel and cart assembly may also be purchased independently (model MS-R and MS-20E). Finally, a telescoping spray wand (model L-5) is also available.

Clean up is easy and maintenance is simple. The MSO uses oilless bearing and stainless steel pump parts. The Dramm MSO Heavy Duty Sprayer is backed by a 6 month parts and labor warranty.

Let the Dramm Heavy Duty Sprayer be your workhorse.



L-5 Lance

Features

- Fully adjustable pressure – up to 500 PSI
- Trigger Gun with adjustable spray pattern and output rates
- Solid bronze & stainless steel pump construction with oilless bearings
- Applies most chemical formulations.
- 33' or 100' Discharge hose
- Optional cart, model MS-20E:
 - 20½" wide with 10" rubber wheels
 - 20 gallon solution tank
 - Bottom draw conversion kit
- Optional hose reel (on model MS20-33)
- Optional telescoping spray-wand

Technical Data

Power Supply	110 V 60 HZ 200 Watts
Horse Power	¼ hp
Maximum Pressure	500 PSI
Maximum Discharge Rate	0.5 GPM
RPM	1800 (no load) 1740 (under Load)
Bearings	Oilless
Drive System	Direct drive
Pump Type	Piston
Plunger Size	Cylinder bore .984" – Stroke .157"
Spray Gun	Adjustable output 0.0 - 0.5 GPM
Discharge Hose Length	33 feet or 100 feet
Suction & Return Hose Length	6 feet
Power Cord Length	8 feet
Spray Distance	Stream: 20 feet Mist: 10 feet

Distributed By:

DRAMM

2000 North 18th Street
P.O. Box 1960
Manitowoc, WI 54221-1960, USA
dramm.com

920-684-0227
Fax: 920-684-4499
information@dramm.com

800-258-0848